

# Rules Resource

Data Dictionary Wiki Version: 1.7

A flexible resource that can be used to transmit business and system rules from host to client application. These rules may be meant for human consumption, e.g. REBR, in which case the client may be a tool allowing a person to review the business rules. The rules may also be meant for machine consumption, e.g. RetsValidation where the rules are structured to be consumed and executed upon by the client application without human intervention. The fields within the Rules Resource include the following:

[ClassName \(Rules\) Field](#)

[FieldKey \(Rules\) Field](#)

[FieldKeyNumeric \(Rules\) Field](#)

[FieldName \(Rules\) Field](#)

[ModificationTimestamp \(Rules\) Field](#)

[OriginalEntryTimestamp \(Rules\) Field](#)

[OriginatingSystemID \(Rules\) Field](#)

[OriginatingSystemName \(Rules\) Field](#)

[OriginatingSystemRuleKey Field](#)

[ResourceName \(Rules\) Field](#)

[RuleAction Field](#)

[RuleDescription Field](#)

[RuleEnabledYN Field](#)

[RuleErrorText Field](#)

[RuleExpression Field](#)

[RuleFormat Field](#)

[RuleHelpText Field](#)

[RuleKey Field](#)

[RuleKeyNumeric Field](#)

[RuleName Field](#)

[RuleOrder Field](#)

[RuleType Field](#)

[RuleVersion Field](#)

[RuleWarningText Field](#)

[SourceSystemHistoryKey \(Rules\) Field](#)

[SourceSystemID \(Rules\) Field](#)

[SourceSystemName \(Rules\) Field](#)